

# CISTERN INSTALLATION BASICS



**Natasha Bailey**  
**Seattle Public Utilities**  
**RainWise Program Manager**



# CISTERN INSTALLATION BASICS

- 1. What is a Cistern?**
- 2. Cistern specifications for RainWise**
  - a. Site Requirements
  - b. Calculating roof area
  - c. Installation Requirements
  - d. RainWise Calculator
- 3. Design Considerations**
- 4. Cistern Purchase Options**



# CONTRACTOR RESOURCES

The image shows a screenshot of the website <https://www.700milliongallons.org/rainwise/contractor-resources/>. The main navigation menu on the left includes: Home, The Goal, RainWise, Projects, Solutions, Tools & Resources, and Events. Under 'Tools & Resources', there are links for 'Contractor Resources' (circled in red) and 'Find a Contractor'. To the right, there are social media links for RainWise and Seattle Public Utilities on Facebook, Instagram, YouTube, and Twitter. A red arrow points from the 'Contractor Resources' link to a detailed page titled 'RainWise Project Paperwork Forms'. This page is divided into two sections: 'Before the Project Starts' and 'Project Completed: Rebate Paperwork'. The 'Before the Project Starts' section lists links for 'RainWise Customer Understanding Form', 'RainWise Infiltration Test Form', 'Sample Site Plan', and 'RainWise Rebate Calculator (Updated July 2022)'. The 'Project Completed: Rebate Paperwork' section lists links for 'RainWise Rebate Checklist for Customers', 'RainWise Rebate Overview Form', 'Vendor Payment Option Form', 'RainWise Property Owner Agreement', '2018 W9 form', 'Rain Garden Warranty Form', 'Cistern Warranty Form', 'Rain Garden Statement of Function Form', 'Cistern Statement of Function Form', and 'Rockery Release Form'. A note at the bottom of this page states: 'For efficiency/ease, here is a consolidated packet of forms that contractors will need to complete with'.

<https://www.700milliongallons.org/rainwise/contractor-resources/>

# WHAT IS A CISTERN?



- Used for the capture and detention of stormwater runoff from roofs
- Used to achieve reductions in peak flows and flow durations during storms
- Can hold water to irrigate landscape as an added benefit



# CISTERN SYSTEM PARTS

## Foundation

- Flat and level surface for cistern installation

## Collection System

- Gutters, downspouts, piping and any other conveyance needed to route runoff from the roof to the cistern.

## Cistern inlet access hatch with screen/debris excluder


- A filter screen or other debris barrier to prevent insects, leaves and other large debris from entering the system

## Overflow outlet

- Outlet pipe located near the top of the cistern to allow the system to overflow to a side sewer or vegetated area in the event of a large storm event

## Flow control outlet and low-flow valve

- Outlet pipe located near the bottom of the cistern. This outlet **must** be open during the rainy season. It allows the cistern to *slowly* drain to the sewer, right of way, or a rain garden. This control valve can be closed in late spring to provide irrigation water for summer.
- Note that this must be installed with at least 4" of area beneath, for sediment to accumulate



# SITE REQUIREMENTS

***See RainWise design specifications***

You will need:


- ✓ A level location near a downspout, outside (not inside a building)
- ✓ To allow enough space for ingress and egress (minimum 3 feet from property line or structure to ensure access to backyard)
- ✓ Compliance with Seattle Department of Construction and Inspection (SDCI) Land Use Code SMC.23.44.014.C.17 requirement regarding the placement of cisterns on private property
- ✓ A solid base (packed gravel, concrete, Versagrid or other approved). Base dimensions will vary by cistern.
- ✓ A safe place to discharge the overflow (after cistern fills)



# SITE REQUIREMENTS

*See RainWise design specifications*


## RAINWISE SITE REQUIREMENTS - CISTERNS



## RAINWISE CISTERN SITE REQUIREMENTS:

1. SUBJECT PARCEL MUST BE IN A QUALIFYING CSO BASIN.
2. A MINIMUM OF 400 SQUARE FEET OF ROOF DRAINAGE AREA MUST BE COLLECTED AND CONVEYED TO RAIN GARDEN AND/OR CISTERN TO QUALIFY FOR REBATE. A MINIMUM OF 300 SQUARE FEET OF ROOF AREA MUST BE COLLECTED AND CONVEYED TO A CISTERN.
3. NO MORE THAN 1,000 SQUARE FEET OF CONTRIBUTING IMPERVIOUS SURFACE MAY OVERFLOW TO CITY SIDEWALK AT A SINGLE LOCATION. SYSTEMS IN EXCESS OF 1,000 SQUARE FEET SHALL HAVE TWO OR MORE OVERFLOWS (AS NECESSARY), EACH SEPARATED BY A DISTANCE OF 10 FEET OR MORE.
4. QUALIFYING CISTERNS MUST BE A MINIMUM OF 200 GALLONS AND A MINIMUM HEAD OF 2.0 FEET. CISTERN LOW FLOW ORIFICE SIZE IS PROJECT SPECIFIC AND MUST MATCH REQUIRED SIZE REPORTED IN THE RAINWISE REBATE CALCULATOR.

# CALCULATING ROOF AREA





# INSTALLATION REQUIREMENTS

## GENERAL NOTES

REFERENCE SHEET **B**  
STANDARD RAINWISE DETAILS  
09/07/2022



### RAINWISE GENERAL NOTES:

1. ALL WORK SHALL CONFORM TO THE CURRENT CITY OF SEATTLE STANDARD SPECIFICATIONS FOR ROAD, BRIDGE, AND MUNICIPAL CONSTRUCTION; THE CITY OF SEATTLE STANDARD PLANS FOR MUNICIPAL CONSTRUCTION, CURRENT EDITION; CITY OF SEATTLE DIRECTORS RULES: 5-2009, 5-2004, 31-2017, 4-2019, 11-2020, 10-2021; AND CODES ADOPTED BY REFERENCE INCLUDING THE SEATTLE BUILDING CODE AND SEATTLE FIRE CODE.
2. A RAINWISE PROJECT MUST MITIGATE RUNOFF FROM AT LEAST 400 SQUARE FEET OF TOTAL ROOF AREA TO QUALIFY FOR A RAINWISE REBATE. A CISTERN MUST COLLECT RUNOFF FROM A MINIMUM OF 300 SQUARE FEET OF ROOF AREA; THERE IS NO MINIMUM ROOF AREA FOR A RAINGARDEN.
3. ROOF DRAINAGE AREAS GREATER THAN 2,000 SQUARE FEET **REQUIRES CONSULTATION WITH RAINWISE INSPECTOR**. ROOF DRAINAGE AREAS GREATER THAN 2,000 SQUARE FEET ARE NOT ELIGIBLE FOR A PRE-INSPECTION WAIVER.
4. ALL DISCHARGE FROM RAIN GARDENS AND/OR CISTERNS MUST BE SAFELY CONVEYED OFF SITE BELOW GROUND IN A SIDE SEWER OR ABOVE GROUND TO THE RIGHT-OF-WAY. DISCHARGE MUST HAVE A SAFE FLOW PATHWAY WITHIN THE RIGHT-OF-WAY TO THE PUBLIC DRAINAGE SYSTEM (MANMADE OR NATURAL) THAT DOES NOT HARM PRIVATE OR PUBLIC PROPERTY OR STRUCTURES.
5. IN ACCORDANCE WITH VOLUME 3, SECTION 4.3 OF COS DIRECTOR'S RULE 10-2021 (SEATTLE STORMWATER MANUAL), OVERFLOW CONVEYANCE MUST SAFELY CONVEY THE 25-YEAR STORM OR GREATER THAN 25-YEAR.
6. ALL CONVEYANCE PIPE DOWNSTREAM OF THE EXISTING DOWNSPOUT MUST MEET RAINWISE REQUIREMENTS.
7. CONNECTIONS TO A SIDE SEWER MAY REQUIRE A SEPARATE SIDE SEWER PERMIT AND INSPECTION. A SIDE SEWER PERMIT AND INSPECTION IS NEEDED IF:
  - THE SIDE SEWER CONNECTION IS NEW, OR
  - THE SIDE SEWER CONNECTION IS MADE BELOW GRADE, OR
  - THE PROJECT RESULTS IN MORE ROOF AREA CONNECTED TO THE SIDE SEWER.
8. DOWNSPOUT TO RAIN GARDEN PIPES SHALL BE A MINIMUM OF 3-INCHES IN DIAMETER. SEE SHEET 3 FOR COMPLETE SIZING REQUIREMENTS.
9. RAIN GARDEN OVERFLOW PIPES SHALL BE A MINIMUM OF 4-INCHES IN DIAMETER. SEE SHEET 7 FOR COMPLETE SIZING REQUIREMENTS.
10. CISTERN OVERFLOW PIPES SHALL BE A MINIMUM OF 3-INCHES IN DIAMETER. SEE SHEET 12 FOR COMPLETE SIZING REQUIREMENTS.
11. PIPE MATERIAL SHALL BE
  - SDR 35 PVC AND SHALL MEET ASTM D 3034,
  - SCHEDULE 40 OR SCHEDULE 80 PVC AND SHALL MEET ASTM D 1785, F 1732, OR D 2729 WITH FITTINGS PER ASTM D 2466 AND D 2467,
  - OR APPROVED EQUAL.
12. FLEXIBLE TUBING OR HOSE MAY ONLY BE USED FOR A PORTION OF CISTERN FLOW CONTROL OUTLET PIPING, SEE SHEET 15. TUBING OR HOSE SHALL BE NON-CLEAR AND UV RESISTANT.
13. DRAIN, WASTE, AND VENT (DWV) PIPING SHALL NOT BE USED. PIPE DUAL MARKED FOR DWV AND PRESSURE APPLICATIONS IS ALLOWED.
14. PER UPC 2.3.3, PIPES SHALL NOT BE EXPOSED TO DIRECT SUNLIGHT. PIPES MAY BE PAINTED BY HOMEOWNER IF THE HOMEOWNER AGREES TO PERFORM SUCH WORK. PAINT SHALL BE APPROPRIATE FOR PIPE MATERIAL TYPE.
15. PIPES NOT FULLY BURIED SHALL BE ANCHORED TO THE GROUND OR AGAINST A WALL TO RESIST MOVEMENT.
16. PER UPC 2.5.2, PIPES SHALL BE SUPPORTED EVERY 4 FEET HORIZONTALLY, AT EVERY CHANGE IN DIRECTION, AT EVERY JOINT, AND EVERY 8 FEET VERTICALLY. PIPE SUPPORTS SHALL BE SECURED TO A FIRM SUBSTRATE. PIPE SUPPORTS SHALL BE DOUBLE-ANCHORED PIPE HANGER STRAPPING, HANGERS, OR APPROVED EQUAL.
17. ALL PIPE AND FITTING JOINTS SHALL BE WATERTIGHT AND GLUED, BONDED, OR MECHANICALLY SECURED AS APPROPRIATE PER PIPE MATERIAL.
18. ANY FLOW CONTROL OUTLET MUST REMAIN OPEN DURING THE WET SEASON (SEPTEMBER TO MAY).
19. CISTERNS WITH HEIGHT GREATER THAN THE NARROWEST DIMENSION (LENGTH, WIDTH, DIAMETER) SHALL BE RESTRAINED, AT INSPECTOR'S DISCRETION, TO PREVENT OVERTURNING.


# CISTERN SECTION

SHEET

9

STANDARD RAINWISE DETAILS

09/07/2022



## GENERAL NOTES:

1. CISTERNS SHALL MEET ALL REQUIREMENTS ON REFERENCE SHEET B AND SHALL BE INSTALLED PER MANUFACTURER RECOMMENDATIONS.
2. ALL CISTERN ENTRANCE LOCATIONS SHALL BE SECURED AS TO BE CHILDPROOF AND TAMPER RESISTANT. A SCREW-ON CISTERN LID MEETS THIS REQUIREMENT.
3. CISTERNS WITH HEIGHT GREATER THAN THE NARROWEST DIMENSION (LENGTH, WIDTH, DIAMETER) SHALL BE RESTRAINED, AT INSPECTOR'S DISCRETION, TO PREVENT OVERTURNING.
4. SYSTEM MUST BE DESIGNED TO PROVIDE ACCESS TO CISTERN AND CISTERN FITTINGS FOR CLEANING AND REMOVAL OF SEDIMENT AND ALGAE. ACCESS SHALL BE THROUGH REMOVABLE LID OR 6 INCH (MINIMUM) INSPECTION PORT. CLEANOUT SHALL BE PROVIDED AT BOTTOM OF TANK (VIA BOTTOM BULKHEAD FITTING).
5. CISTERNS OVER 6.5 FEET TALL OR WITH STORAGE CAPACITY GREATER THAN 1,100 GALLONS REQUIRE CONSULTATION AND PRE-INSPECTION WITH RAINWISE INSPECTOR.
6. ALL CISTERN PIPING MATERIALS SHALL BE RIGID. 12 LINEAR INCHES OF 2 INCH (MAXIMUM) DIAMETER FLEXIBLE PIPE MAY BE USED TO CONNECT TERMINUS OF FLOW CONTROL OUTLET TO OVERFLOW PIPING.
7. OVERFLOW AND LOW FLOW PIPE CONFIGURATIONS (FITTINGS AND PIPE LENGTH) MAY VARY BY CISTERN, SEE SHEET 12. PIPE SUPPORT TO BE PROVIDED PER REFERENCE SHEET B.
8. PLASTIC CISTERNS MUST BE UV STABILIZED. ALL CISTERNS MUST BE NON-COLLAPSIBLE, WATERTIGHT, AND OF DURABLE MATERIAL TO PROVIDE A LONG SERVICE LIFE.
9. TO PREVENT FREEZING DAMAGE, ALL EXPOSED PIPE MUST BE FREE DRAINING.
10. PROVIDE WATER TIGHT FITTINGS AT ALL CISTERN CONNECTIONS.
11. LOCATE CISTERNS TO AVOID OBSTRUCTION OF UTILITIES, WINDOWS, OR OTHER SITE FEATURES THAT REQUIRE ACCESS.
12. SEE REFERENCE SHEET D FOR CISTERN SETBACK REQUIREMENTS.
13. SEE SHEET 13 FOR DESIGN REQUIREMENTS FOR CISTERNS IN SERIES.
14. INSTALL A REMOVABLE CAP ON ALL BELOW GROUND DOWNSPOUTS CUT FOR PROJECT INSTALLATION. SEE SHEET 3 FOR AN EXAMPLE.

# MAKE THE CONNECTION



## NOTES:

1. PROVIDE DEBRIS EXCLUDER WITH 1/16 INCH MAXIMUM MESH SCREEN SIZE AT CISTERN INLET. PROVIDE 3-INCH VERTICAL GAP BETWEEN DOWNSPOUT AND CISTERN INLET. DEBRIS EXCLUDER SHALL BE MAINTAINABLE AND LOCATED TO PROVIDE MAINTENANCE ACCESS. DEBRIS EXCLUDER AT CISTERN INLET MAY BE SUPPLEMENTED WITH A DOWNSPOUT FILTER OR DIVERTER TO REDUCE MAINTENANCE NEED.

# PIPE MATERIAL & SUPPORT


- Pipes in contact with the ground shall be schedule 40 PVC or approved equal
- Pipes not in contact with the ground shall be PVC schedule 40, SDR 35, or ABS
- All pipe and fitting joints shall be watertight and glued, bonded, or mechanically secured.
- Pipes shall be **supported** every 4 ft Horizontal, at changes in direction, and every 8 ft vertical




# CISTERN OUTLETS

## CISTERN OUTLETS


SHEET 12  
STANDARD RAINWISE DETAILS  
09/07/2022




OPTION 1: EXTERNAL OVERFLOW OUTLET (PREFERRED)



OPTION 2: INTERNAL OVERFLOW WITH RISER (SNORKEL) OUTLET



FLOW CONTROL OUTLET MODIFICATION FOR (SNORKEL) CISTERNS WITHOUT 4 INCH SUMP



**NOTES:**

1. CONNECTIONS TO SIDE SEWER MAY REQUIRE A SEPARATE SIDE SEWER PERMIT AND INSPECTION, SEE SHEET 14.
2. MINIMUM PIPE DIAMETER AND ASSOCIATED FITTING SIZE VARIES BASED ON CONTRIBUTING AREA AS FOLLOWS:
  - UP TO 2,000 SQUARE FEET: 3 INCH DIAMETER
  - 2,000 TO 3,000 SQUARE FEET: 4 INCH DIAMETER
3. CLEARANCE AT TOP OF OVERFLOW VARIES BASED ON OVERFLOW PIPE DIAMETER AS FOLLOWS:
  - 3 INCH PIPE DIAMETER: PROVIDE 4 INCHES CLEARANCE
  - 4 INCH PIPE DIAMETER: PROVIDE 5 INCHES CLEARANCE

**GENERAL NOTE:**

1. PROVIDE MODIFIED FLOW CONTROL OUTLET (SNORKEL) FOR CISTERNS MANUFACTURED WITH SUMPS LESS THAN 4 INCHES, DETAIL THIS SHEET.

# OVERFLOW OUTLET

***See RainWise design specifications***

- Allows stormwater exceeding the cistern capacity to overflow to an approved point of discharge by gravity flow.
- Must include a removable bulkhead fitting
- Pipe must be 3-4" in diameter
- Pipe must have 4-5" of clearance
- Connection may require a side sewer permit
- On the specs, see Sheet 10


## NOTES:

1. CONNECTIONS TO SIDE SEWER MAY REQUIRE A SEPARATE SIDE SEWER PERMIT AND INSPECTION, SEE SHEET 14.
2. MINIMUM PIPE DIAMETER AND ASSOCIATED FITTING SIZE VARIES BASED ON CONTRIBUTING AREA AS FOLLOWS:
  - UP TO 2,000 SQUARE FEET: 3 INCH DIAMETER
  - 2,000 TO 5,000 SQUARE FEET: 4 INCH DIAMETER
3. CLEARANCE AT TOP OF OVERFLOW VARIES BASED ON OVERFLOW PIPE DIAMETER AS FOLLOWS:
  - 3 INCH PIPE DIAMETER: PROVIDE 4 INCHES CLEARANCE
  - 4 INCH PIPE DIAMETER: PROVIDE 5 INCHES CLEARANCE




# OVERFLOW OUTLET

## OPTION 1: EXTERNAL OVERFLOW OUTLET (PREFERRED)




## OPTION 2: INTERNAL OVERFLOW WITH RISER OUTLET




# FLOW CONTROL OUTLET

- Allows the cistern to discharge to a rain garden, right of way or back into the side sewer.
- Minimum diameter shall be 1", and shall match manufacturer's bulkhead fitting diameter
- Must provide a minimum 4" sump
- Includes the "low-flow kit"
- Additionally, if your overflow pipe is connecting back into a side sewer, a separate side sewer permit may be required.
- On the specs, see Sheet 12 & 15





# FLOW CONTROL OUTLET – LOW FLOW KIT



# FLOW CONTROL OUTLET - CLEANOUT



# SIDE SEWER CONNECTIONS



- A side sewer permit may be required when RainWise contractors are working on a side sewer.
- The RainWise Program puts the sole responsibility on the Rain Wise contractor to abide and comply with all Side Sewer permit processes and requirements.
- For more information on the Seattle Department of Construction & Inspections (SDCI) Side Sewer Permit, including how to apply, visit:  
[https://www.seattle.gov/sdci/permits/permits-we-issue-\(a-z\)/side-sewer-permit](https://www.seattle.gov/sdci/permits/permits-we-issue-(a-z)/side-sewer-permit)

# CISTERN FOUNDATIONS

CISTERN FOUNDATION (1 OF 2)

SHEET **10**  
STANDARD RAINWISE DETAILS  
09/07/2022



*IN PROGRESS*

# CISTERN FOUNDATIONS

There are 4 primary options for cistern foundations

- Timber frames
- Plastic gravel pavers
- Soil frames
- Cement foundation



# CISTERN FOUNDATIONS



# CISTERN RESTRAINTS



3. CISTERNS WITH HEIGHT GREATER THAN THE NARROWEST DIMENSION (LENGTH, WIDTH, DIAMETER) SHALL BE RESTRAINED, AT INSPECTOR'S DISCRETION, TO PREVENT OVERTURNING.

# RAINWISE CALCULATOR



HOME THE GOAL RAINWISE ▾ PROJECTS ▾ SOLUTIONS ▾ RAINCITY TOOLS & RESOURCES

## Before the Project Starts

Before construction begins on a RainWise project, contractors are responsible for the completion of these forms.

- [RainWise Customer Understanding Form](#)
- [RainWise Infiltration Test Form](#)
- [Sample Site Plan](#)
- [RainWise Rebate Calculator \(Updated September 2022\)](#)

<https://www.700milliongallons.org/rainwise/contractor-resources/>



# RainWise Sizing and Rebate Calculator

Contractor Name

Client Name

Project Address

Notes

Contributing Roof Area  sf

Project Type

## Cistern

No. Connected Cisterns

Cistern Type <sup>3</sup>

Cistern Overflow Height <sup>4</sup>  ft

Total Cistern Height <sup>5</sup>  ft

Single Cistern Volume <sup>6</sup>  gal

Cistern Diameter <sup>7</sup>  in

## RainWise Rebate

% Construction Rebate	→	<input type="text" value="0%"/>	Enter contributing roof area per square foot contributing area
Construction Rebate Rate <sup>8,9</sup>	→	<input type="text" value="\$0.00"/>	
Total Rebate	→	<input type="text" value="\$0.00"/>	
Gallons Managed Annually <sup>10</sup>	→	<input type="text" value="0"/>	gallons
Required Orifice Size <sup>11</sup>	→	<input type="text" value="N/A"/>	

# DESIGN CONSIDERATIONS



## **Pumps**

- Many cistern customers are interested in pumps to make summer watering easier.
  - Many options are available (including solar-powered ones).
- Pumps are not covered by the RainWise rebate, but Contractor can help with pump installation separate from rebate.

## **Aesthetic Options**

- art, landscaping, or fencing



# CISTERN PURCHASE OPTIONS



## Seattle Vendors for Cistern & Rain Garden Plumbing Supplies

There are variances depending on price, selection, and buying in bulk versus single purchases, and convenience of location. Contractors should call to see which is the best deal depending on their needs. If you are aware of a plumbing vendor we have missed, please contact [rainwise@seattle.gov](mailto:rainwise@seattle.gov).

**Ferguson Plumbing Supply**  
206-767-7700  
[1100 W Marginal Way SW, Seattle, WA 98106](http://1100-W-Marginal-Way-SW-Seattle-WA-98106)

**McClendon Hardware**  
206-762-4090  
[10210 16th Ave SW, Seattle, WA 98146](http://10210-16th-Ave-SW-Seattle-WA-98146)

**Keller Supply Co**  
206-340-0800  
[737 5 Stacy St, Seattle, WA 98134](http://737-5-Stacy-St-Seattle-WA-98134)

**H D Fowler Company**  
253-863-8600  
[1417 Thornton Ave SW, Pacific, WA 98047](http://1417-Thornton-Ave-SW-Pacific-WA-98047)

**Pacific Plumbing Supply Company LLC**  
North: 206-864-2900  
[12725 Milvada Ave N, Seattle, WA 98133](http://12725-Milvada-Ave-N-Seattle-WA-98133)  
South: 206-762-5920  
[7115 W Marginal Way SW, Seattle, WA 98106](http://7115-W-Marginal-Way-SW-Seattle-WA-98106)

**Seattle Conservation Corps**  
*Seattle Parks and Recreation has a variety of products for sale to RainWise contractors through the Seattle Conservation Corps, including cisterns and low-flow kits.*  
<https://www.seattle.gov/Documents/Departments/ParksAndRecreation/Business/RainTanks.pdf>  
206-684-0190  
[7727 63rd Ave, NE, Suite 201](http://7727-63rd-Ave-NE-Suite-201)

**Morgan's Kitchen, Bath, Electric & Plumbing**  
206-789-3205  
[8055 15th Ave NW, Seattle, WA 98117](http://8055-15th-Ave-NW-Seattle-WA-98117)

**Stoneway Hardware**  
Wallingford (PERMANENTLY CLOSED)  
Ballard: 206-724-0571  
[4910 15th Ave NW, Seattle, WA 98107](http://4910-15th-Ave-NW-Seattle-WA-98107)

**Grainger Industrial Supply**  
800-471-4643  
[1100 W Marginal Way SW, Seattle, WA 98106](http://1100-W-Marginal-Way-SW-Seattle-WA-98106)

**Home Depot (Various Locations)**  
*Typically carry 3" and 4" PVC and ABS schedule 40 parts and pipes*  
Bellevue: 425-451-7331  
Downtown Seattle: 206-467-9300  
North Seattle: 206-361-9600  
West Seattle: 206-762-2126  
Shoreline: 206-546-1900  
Tukwila: 206-575-9200

**Lowes (Various Locations)**  
*Typically carry 3" and 4" PVC and ABS schedule 40 parts and pipes, plus some carry a lighter weight foam core 3" schedule 40 pipe.*  
South Seattle: 206-760-0832  
North Seattle: 206-366-0365  
Lynnwood: 425-744-8411  
Renton: 425-757-5520  
Tukwila: 206-243-5470  
Kent: 206-651-9036

For more information, please visit: [700milliongallons.org/rainwise/contractor-resources/](http://700milliongallons.org/rainwise/contractor-resources/)

## Cistern Distributors

One of the benefits of coordinating bulk orders on cisterns with other contractors is saving on shipping fees. Price and selection between the below vendors will vary. Please contact these distributors for more information. If your name is not on the list, but you are a distributor for a Rainwater harvesting tank manufacturer and are interested in coordinating bulk orders with other contractors, please contact [rainwise@seattle.gov](mailto:rainwise@seattle.gov).

### Bushman/Norwesco

David Hymel  
*Rain Dog Designs*  
(253) 389-2060 (cell)  
[RainDogDesigns.com/Wordpress](http://RainDogDesigns.com/Wordpress)

Tim Griffen  
*Monsoon Rain Gardens*  
*A Division of Garden Seasoning, Inc.*  
206-782-0418  
[www.monsoonraingardens.com](http://www.monsoonraingardens.com)

Some of the Plumbing Supply vendors listed on Page 1 may have Bushman/Norwesco tanks in stock. Contact them for pricing and availability.

Norwesco/Bushman tanks may also be shipped directly to the client's home. Shipping fees apply.

### Premier Plastics Inc.

Jim Bristow  
*Bristow Enterprises*  
206-841-1964  
[jameseb63@gmail.com](mailto:jameseb63@gmail.com)

Premier Plastics tanks may also be available through Keller Supply and H D Fowler Company.

### Cypress Designs

Seattle Conservation Corps  
*Seattle Parks and Recreation offers a variety of products for sale to RainWise contractors through the Seattle Conservation Corps. Contact Penny for sizes and availability.*  
206-684-0190  
[7727 63rd Ave, NE, Suite 201](http://7727-63rd-Ave-NE-Suite-201)

<https://www.700milliongallons.org/rainwise/contractor-resources/>

# CISTERN PURCHASE OPTIONS



- Partnership with **Seattle Parks & Recreation** and **Seattle Conservation Corps (SCC)**
- Warehouse located at Magnuson Park 7727 63rd Ave NE Seattle, WA 98155
- RainWise will invoice you within 60 days; payment is due within 30 days
- **NEW in 2022:** Cypress Design cisterns manufactured in Bellingham, Washington Available exclusively for RainWise contractors
- Additional cisterns available for purchase directly through the SCC
- To learn more about the process for purchasing, see the RainWise Cistern Invoice Process at <https://www.700milliongallons.org/rainwise/contractor-resources/>



**Seattle**  
Parks & Recreation



# CISTERN INSTALLATION BASICS SUMMARY



- 1. What is a Cistern?**
- 2. Cistern specifications for RainWise**
  - a. Site Requirements
  - b. Calculating roof area
  - c. Installation Requirements
  - d. RainWise Calculator
- 3. Design Considerations**
- 4. Cistern Purchase Options**

# CISTERN INSTALLATION BASICS



Rex Davis  
Seattle Public Utilities  
Inspections Lead



Sabine Jessel  
King County  
Inspections Lead



Natasha Bailey  
[Natasha.Bailey@seattle.gov](mailto:Natasha.Bailey@seattle.gov)  
206.586.2297

Q&A